

**PRESTACIONES ESPECIALES**

- Multi-modo auto búsqueda de canales (AUTO/FTA/Network/TP).
- Máximo almacenamiento 3000 Canales, 2000 Transpondedores, 150 Satélites.
- EPG.
- Transparencia de OSD ajustable.
- Colores de OSD alternativos.
- Zoom de imagen.
- 4 grupos de lista favoritos definidos por separado de fácil manejo.
- Búsquedas Multi-modo.
- Teletexto con inserción VBI.
- DiSEqC 1.0 y DiSEqC 1.2 controles compatible.
- Indicador de señal en tiempo real.
- Pausa de imagen.
- Retrosceso canal anterior
- Apagado automático.
- Directorio Telefónico (opcional).
- Video Juegos (snack, gobang) (opcional).

**PRESTACIONES BÁSICAS**

- Free-to-Air Compatible.
- Tuner de alta sensibilidad.
- Display 4-dígitos 7-segmentos.
- Totalmente compatible DVB-S/MPEG2.
- SCPC/MCPC, C-band/Ku-band Compatible.
- OSD Multi-lenguaje.
- 13V/18V, 22KHz, DiSEqC1.0, DiSEqC1.2 Switching.
- Cambio rápido de canales.
- Función Control Paterno.
- Detección Automática PAL / NTSC.
- Salida RF, Salida AV, Entrada RF.
- Actualizaciones de software (DFU&DFA) PC a Receptor, Receptor a Receptor
- Menu de 256 colores

## ESPECIFICACIONES

**LNB / TUNER**

Satellite IF Input: 950-2150MHz  
Input impedance: 75Ohm  
Signal Level: 65 dBm--25 dBm  
Connector: F type, Female, Loop Through  
LNB power supply: 13/18V/OFF, MAX.400mA  
Band switch: 22KHz Tone

**Demodulation**

Standard: DVB-S EN300 421  
Waveform: QPSK  
Symbol rate: 2-45 MS/s  
Roll off factor: 0.35  
Reed Solomon decoder: Rs232  
Code rate: 1/2, 2/3, 3/4, 5/6, 7/8

**Video decoder**

Standard: CD ISO/IEC 13818-2, MPEG-2 MP@ML  
Video aspect ratio: 4:3, 16:9  
Video system: PAL and NTSC

**Audio decoder**

Standard: ISO/IEC 11172-3  
Audio decoder: MPEG-1 Layer I and II  
Audio channel: Mono, Dual-channel, Stereo, Joint Stereo  
Volume control: 32 Levels adjustment

**Connector**

RF output: 21-69 CH with PLL  
Audio output: 2 X RCA  
Video output: 1 X RCA  
Scart terminal: 1

**General Data**

Operating Temp.: 0° ~ 40° C  
Power supply: AC 90 ~ 260V, 50~60Hz  
Dimensions: 300 (W) X 210 (D) X 64(H)  
Weight: 2.0Kg

The above specifications are subject to change without notice.

